



## Details

- Specifically designed to carry heavy cargo that is best loaded from above or for cargo that exceeds the height of the container commonly known as "out of gauge"
- Removable tarpaulin, removable roof bows
- Roof opening may vary depending on type of construction
- Some models also have a swinging header (rear top rail) to facilitate easier loading operations

### OUTSIDE DIMENSIONS

|        |    |       |
|--------|----|-------|
| length | mm | 12192 |
|        | ft | 40'   |
| width  | mm | 2438  |
|        | ft | 8'    |
| height | mm | 2591  |
|        | ft | 8' 6" |

### ROOF OPENING

|        |    |             |
|--------|----|-------------|
| width  | mm | 11544       |
|        | ft | 37' 10 1/2" |
| height | mm | 2230        |
|        | ft | 7' 3 3/4"   |

### INSIDE DIMENSIONS

|          |      |            |
|----------|------|------------|
| length   | mm   | 12029      |
|          | ft   | 39' 5 1/2" |
| width    | mm   | 2342       |
|          | ft   | 7' 8 1/8"  |
| height   | mm   | 2326       |
|          | ft   | 7' 7 1/2"  |
| capacity | cbm  | 65.5       |
|          | cbft | 2310       |

### WEIGHTS

|              |    |       |
|--------------|----|-------|
| Tare         | kg | 3810  |
|              | pd | 8400  |
| Max. payload | kg | 26670 |
|              | pd | 58800 |
| Max. Gross   | kg | 30480 |
|              | pd | 67200 |

### DOOR OPENING

|                  |    |           |
|------------------|----|-----------|
| width            | mm | 2336      |
|                  | ft | 7' 8"     |
| height           | mm | 2280      |
|                  | ft | 7' 5 3/4" |
| width side door  | mm | ./.       |
|                  | ft | ./.       |
| height side door | mm | ./.       |
|                  | ft | ./.       |

### CERTIFICATION

|                |      |
|----------------|------|
| ISO size type  | 42U1 |
| ISO size group | 42UT |